



The North American Collection

“WISCONSIN” ROUND SHALLOW (Selectable Wattage/CCT Series)

Indoor/Outdoor — Vandal Wall Pack Family | Selectable Wattage / CCT



Greenbay (GB)




Kenosha (KN)



Milwaukee (ML)



Hudson (HU)



SELECTABLE LED WATTAGE / LUMENS

Selectable LED Wattage / Lumen Output		
Low Power	Medium Power	High Power
13.5 Watt (2150 Lumens)	17 Watt (2400 Lumens)	20.5 Watt (3150 Lumens)

Note: Lumen output based on 4000K CCT.

Catalog Number

Project Name & Location

Type

Product Specifications

DIFFUSER: Smooth Opal White Injection Molded Polycarbonate standard. Optional Frosted Opal Lens (FRO).

DRIVER: Universal Voltage 120/277v Electronic Driver with 0-10V dimming.

EMERGENCY: Optional Integral or Remote LED Emergency Battery

FASTENERS: (4) Stainless steel tamperproof Torx screws to secure lens to backplate.

FINISH: Extremely durable oven baked Polyester Powder Coat is Standard.

GASKETING: One Piece Die Cut 3/16" Thick Black EPDM.

HOUSING: Marine Grade cast aluminum.

LIGHT ENGINE: Energy Efficient Light Emitting Diode - Selectable Wattage/CCT.

MOUNTING HOLES: (4) 5/16" Diameter Holes for 1/4" Diameter Bolts.

COMPLIANCE: Built to comply with U.S. and Canadian Safety Standards. Suitable for Wet Locations.

WARRANTY: 5-Year Limited Warranty.

order example:

KN-4-SLED-SCCT-UNV-BK-FRO

SERIES

GB Greenbay Series

HU Hudson Series

KN Kenosha Series

KN-F Kenosha Flat Lens Series

ML Milwaukee Series

SIZES

4 13.75" Diameter Height x 4" Depth

—ADA Compliant

—Not for Use with Side Conduit Entry

LED WATTAGES

Note: Refer to Chart for Lumen Output

SLED *Selectable LED Wattage: 13.5W | 17W | 20.5W

LED COLOR TEMPERATURE (CCT)

SCCT *Selectable CCT: 3000K | 3500K | 4000K | 5000K

VOLTAGES

UNV 120-277 Universal Volt Driver

STANDARD FINISH

BK Black

WHT Textured White

PREMIUM UPCHARGE FINISH

Note: Premium Finishes Require MOQ = 5pcs

BZ Bronze

PA Painted Aluminum

CC Custom Color (Visit www.ralcolor.com)

—Provide RAL# or Make-to-Match Color Chip

INHIBITOR FINISH

Note: Inhibitor Finishes Require MOQ = 5pcs

+NAT Epoxy Coating for Natatorium

+OFC Epoxy Coating for Ocean Front Environments

LENS OPTIONS

FRO Frosted Opal

RC Ribbed Clear

RF Ribbed Frosted

RW Ribbed White

MISC OPTIONS

FUS Fuse and Fuseholder

EMERGENCY BATTERY OPTIONS

• Meets California Energy Commission Title 20 [CEC-400-2014-009-CMF] Efficiency Standards

—Cold Weather Batteries DO NOT meet CEC Standards

• Cold Weather Emergency Batteries Temp Range:

-20°C thru 50°C

• Max Whip Length for REM Option is 8 Feet

REM8W Remote 8 Watt LED

REM10W Remote 10 Watt LED

REM16W Remote 16 Watt LED

REM10W- Remote 10 Watt LED - Cold Weather

CW

ACCESSORY OPTIONS

Order As A Separate Line

TPD Tamperproof Screwdriver

*NOTE: Fixtures will ship from factory at lowest wattage and warmest CCT. It is the installer's responsibility to set the fixture at the desired wattage and CCT for their project.

The North American Collection

“WISCONSIN” ROUND SHALLOW (Static Wattage/CCT Series)

Indoor/Outdoor — Vandal Wall Pack Family | Static Wattage / CCT (Non-Selectable)



Greenbay (GB)




Kenosha (KN)



Milwaukee (ML)



Hudson (HU)



order example:

KN-4-LED25-CT4-UNV-BK-FRO-OCC

SERIES

GB Greenbay Series

HU Hudson Series

KN Kenosha Series

KN-F Kenosha Flat Lens Series

ML Milwaukee Series

SIZES

4 13.75" Diameter Height x 4" Depth
– ADA Compliant
– Not for Use with Side Conduit Entry

LED WATTAGES

LED25 *25 Watt LED (Static Wattage - Non-Selectable)

LED COLOR TEMPERATURE (CCT)

CT3 ±3000K LED Color Temp

CT35 ±3600K LED Color Temp

CT4 ±4000K LED Color Temp

CT5 ±5000K LED Color Temp

VOLTAGES

UNV 120-277 Universal Volt Driver

STANDARD FINISH

BK Black

WHT Textured White

PREMIUM UPCHARGE FINISH

Note: Premium Finishes Require MOQ = 5pcs

BZ Bronze

PA Painted Aluminum

CC Custom Color (Visit www.ralcolor.com)

– Provide RAL# or Make-to-Match Color Chip

INHIBITOR FINISH

Note: Inhibitor Finishes Require MOQ = 5pcs

+NAT Epoxy Coating for Natatorium

+OFC Epoxy Coating for Ocean Front Environments

LENS OPTIONS

FRO Frosted Opal

RC Ribbed Clear

RF Ribbed Frosted

RW Ribbed White

MISC OPTIONS

FUS Fuse and Fuseholder

SENSOR CONTROL

Note: Motion Sensor Max Mounting Height 18-Feet

OCC Occupancy Sensing / Motion Sensor Integral
– Microwave / Single Feed / 120/277 Only
– Stand-by Dimming Level Presets: ON/OFF

EMERGENCY BATTERY OPTIONS

• Meets California Energy Commission Title 20 [CEC-400-2014-009-CMF] Efficiency Standards

– Cold Weather Batteries DO NOT meet CEC Standards

• Cold Weather Emergency Batteries Temp Range:

–20°C thru 50°C

• Max Whip Length for REM Option is 8 Feet

REM8W Remote 8 Watt LED

REM10W Remote 10 Watt LED

REM16W Remote 16 Watt LED

REM10W-CW Remote 10 Watt LED - Cold Weather CW

ACCESSORY OPTIONS

Order As A Separate Line

TPD Tamperproof Screwdriver

Catalog Number

Project Name & Location	Type
-------------------------	------

Product Specifications

DIFFUSER: Smooth Opal White Injection Molded Polycarbonate standard. Optional Frosted Opal Lens (FRO).

DRIVER: Universal Voltage 120/277v Electronic Driver with 0-10V dimming.

EMERGENCY: Optional Integral or Remote LED Emergency Battery

FASTENERS: (4) Stainless steel tamperproof Torx screws to secure lens to backplate.

FINISH: Extremely durable oven baked Polyester Powder Coat is Standard.

GASKETING: One Piece Die Cut 3/16" Thick Black EPDM.

HOUSING: Marine Grade cast aluminum.

LIGHT ENGINE: Energy Efficient Light Emitting Diode - Static Wattage/CCT (Non-Selectable).

MOUNTING HOLES: (4) 5/16" Diameter Holes for 1/4" Diameter Bolts.

COMPLIANCE: Built to comply with U.S. and Canadian Safety Standards. Suitable for Wet Locations.

WARRANTY: 5-Year Limited Warranty.